

REPORT DOCUMENTATION PAGE				Form Approved OMB No. 0704-0188	
<p>Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing this collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.</p>					
1. REPORT DATE (DD-MM-YYYY) May 2012		2. REPORT TYPE Viewgraph		3. DATES COVERED (From - To) May 2012- July 2012	
4. TITLE AND SUBTITLE Coherent Rayleigh-Brillouin Scattering in High Intensity Laser Fields (Briefing Charts)				5a. CONTRACT NUMBER In-House	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER 65502F	
6. AUTHOR(S) Barry Cornella, Sergey Gimelshein, Taylor Lilly, and Andrew Ketsdever				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER 50260542	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Air Force Research Laboratory (AFMC) AFRL/RQRC 10 E. Saturn Blvd. Edwards AFB CA 93524-7680				8. PERFORMING ORGANIZATION REPORT NO.	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) Air Force Research Laboratory (AFMC) AFRL/RQR 5 Pollux Drive Edwards AFB CA 93524-7048				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S) AFRL-RZ-ED-VG-2012-218	
12. DISTRIBUTION / AVAILABILITY STATEMENT Distribution A: Approved for Public Release; Distribution Unlimited. PA#12507					
13. SUPPLEMENTARY NOTES Conference paper for the 2012 American Physical Society Meeting of the Division of Atomic, Molecular and Optical Physics, Orange County, California in 4-8 July 2012.					
14. ABSTRACT We have performed coherent Rayleigh-Brillouin scattering (CRBS) experiments on collisional gasses subject to laser intensities beyond those considered perturbative to the gasses' thermodynamic parameters. CRBS is a four wave mixing scheme traditionally used for gas diagnostic applications when utilizing low intensity laser pulses. In these experiments high intensity laser pulses are used which yield signal lineshapes inconsistent with perturbative theory. Gas heating, weak ionization, and three dimensional effects are discussed as possible nonlinear optical effects which would have to be accounted for in order to model the high intensity regime. The cause of this altered lineshape may furthermore be used to diagnose the full effect of the laser pulses on the gas.					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT SAR	18. NUMBER OF PAGES 9	19a. NAME OF RESPONSIBLE PERSON Marcus Young
a. REPORT Unclassified	b. ABSTRACT Unclassified	c. THIS PAGE Unclassified			19b. TELEPHONE NO (include area code) 661-275-6264



Coherent Rayleigh-Brillouin Scattering in High Intensity Laser Fields: Optical Lattice Gas Heating



Barry Cornella and Sergey Gimelshein,
ERC Inc., Edwards AFB, CA 93524, USA,



Taylor Lilly
University of Colorado, Colorado Springs, CO 80918, USA

Andrew Ketsdever
Air Force Research Laboratory, Edwards AFB, CA 93524, USA



DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited



Coherent Rayleigh-Brillouin Scattering



- Pulsed four-wave mixing scheme used for gas diagnostics
- Low intensity
 - Perturbative regime (small perturbations)
 - Scattering spectra predicted by simplified gas dynamic model
- High intensity
 - Complex collision and forcing term
 - Cannot be predicted by simplified model (must be statistically simulated)
- Experimentally prove gas heating via optical lattices





Experimental/Numerical Setup






Experimental

- Narrowband pump beams (~45 μm dia.)
- Frequency difference between pumps swept to vary lattice velocity
- Low speed gas jet placed at interaction region
- Signal magnitude measured on high speed oscilloscope

Numerical

- Modified version of a DSMC code SMILE used to simulate particles within optical lattice
- Parameters chosen for direct comparison with experiment
- Density perturbation found through non-linear least squares fit
- Domain represents centerline of laser pulse






CRBS Results




Low Intensity

N_2 ($I = 3 \times 10^{14} \text{ W/m}^2$)



High Intensity


N_2 ($I = 1 \times 10^{16} \text{ W/m}^2$)





- **Experiment and DSMC show good agreement with six-moment model (s6) for low intensity**
(X. Pan, "Coherent Rayleigh-Brillouin scattering," Princeton University (Ph.D. Thesis, 2003))
- **Possible causes of narrowing at higher intensities include:**
 - Partial ionization (not lattice velocity dependent)
 - Gas dissociation (not lattice velocity dependent)
 - **Gas heating** (lattice velocity dependent)



DSMC Heating Prediction





- Peak centerline temperature increase of 51 K at lattice velocity = 450 m/s
- Temperature varies radially with I^2
- Average volume temperature (laser FWHM $\sim 45 \mu\text{m}$ dia.) of 330 K






Experimental Energy Deposition



- Detects IR probe beam deflection due to refractive index change caused by pressure wave expansion
- Magnitude of photodiode signal proportional to strength of pressure wave
- Measurements taken vs. probe beam offset and lattice velocity



Speed of sound:

N_2


- Calculated: $a = 353$ m/s
- Measured: $a = 361$ m/s (+2.3%)

CH_4

- Calculated: $a = 450$ m/s
- Measured: $a = 464$ m/s (+3.1%)



IR Probe Results



- Temperature profile normalized by maximum (trend only)
- Peak locations vary by ~40 m/s (~9%)
 - DSMC assumes max intensity
 - Laser beam alignment
 - Pump timing



Summary



- **High Intensity CRBS effects:**
 - Partial ionization (Not lattice velocity dependent)
 - Gas dissociation (Not lattice velocity dependent)
 - **Gas heating** (Lattice velocity dependent)
- **Local gas heating shown in high intensity CRBS due to lattice interaction**
 - Numerically predicted
 - Experimentally verified by pressure wave detection with IR probe
 - Experiment and numerical simulations show good agreement

